

INTERACTIVE TOOLS

The ActiView 324 visual presenter enables printed materials and objects to be viewed and shared with the entire class. This offers opportunities for collaboration in the classroom as it facilitates the sharing of information and work, as well as enabling students to engage collectively with 3D objects. Uniquely integrated with ActivInspire software, images can be annotated over and saved in flipchart format or images and video can be automatically inserted into flipchart pages.

MINIMUM COMPUTER REQUIREMENTS

Operating Systems	For Use with ActivInspire PC: Windows XP SP 3 and above (XP/Vista/7/8) Macintosh: OSX 10.6.8 – 10.8.1 (Snow Leopard/Lion/Mountain Lion) Linux Ubuntu 12.04
PC	Pentium 4 – 1 GHz processor (800MHz for Vista), 512 MB of RAM, 1024x768 resolution, 1.5 GB of Free Disk Space
Mac	Intel Processors (Universal Binary), 512 MB of RAM, 1024x768 resolution, 3.0 GB of Free Disk Space



SPECIFICATIONS

Output Resolution	XGA (1024 x 768), SXGA (1280 x 1024), UXGA (1600 x 1200), 1080p
Frame Rate	30 fps maximum
Zoom Capacity	9x Mechanical and 12x Digital Zoom
Capture Area	442mm x 331mm (17.4in x 13in)
Lamp Type	Integrated LED
Lamp Life	Up to 20,000 hours
Number of Lamps	One integrated light; One light on independent gooseneck
Power Supply	Built-in; 100-240 VAC, auto switching
VGA Pass Thru Max Display Mode	Active pass-through, up to UXGA 60 Hz; VGA In and VGA Out
VGA In	1 In
VGA Out	2 ports to projector/computer and to monitor for VGA pass-thru
USB	USB 2.0 High Speed (up to 480 Mbps)
Composite Video Out	RCA Jack, NTSC/PAL
HDMI	Yes (with Audio)
RS232	Yes (extender)

CONTINUED ON NEXT PAGE

ActiView 324 SS 02/14 V1.2

©2014 Promethean Limited. All rights reserved. Promethean Ltd. is owner of a number of trademarks in several jurisdictions across the world. Any third-party product and company names are mentioned for identification purposes only and may be trademarks of their respective owners. ¹Applicable Terms and Conditions for warranty and support available at www.PrometheanWorld.com/ActivCare. All dimensions +/- 5mm (0.2in). All weights +/- 0.9kg (2lb). Product Specifications are subject to change without notice. www.PrometheanWorld.com

SPECIFICATIONS (CONTINUED)

Microphone	Yes
Internal Memory	240 JPEG images
Image Capture	Supports SDHC/SDXC cards up to 64GB; Capture images to internal memory or to the computer via USB connection
Image Rotation	Full screen image rotation from 0 to 90, 180 to 270 degrees
Video Capture	Video recording to computer or built-in memory with various compression codecs
Pan	Automatically zoom from full page to separate quadrants
Security	Auto Erase Mode (option to automatically erase internal memory during power down); Kensington lock slot available; VESA standard to mount to a surface
Certifications/Compliance	FCC-EMI, cUL, CE-EMC, CE-LVD, RoHS and WEEE
Weight	2.38 Kg (5.2 lbs)
Packed Weight	3.15 Kg (6.9lbs)
Dimension	420mm x 140mm x 395mm (16.5in x 5.5in x 15.6in) (LxWxH)
Languages	Brazilian Portuguese, Chinese (Traditional & Simplified), Danish, Dutch, English, Finnish, French, German, Italian, Polish, Portuguese, Russian, Spanish and Swedish
Packed Contents List	US/UK/EMEA power leads, VGA, USB and Composite video cables, microscope adapter, remote control, CD, Quick Start Guide and User Manual

WARRANTY AND SUPPORT[†]

Warranty	For Promethean Warranty Information please visit: www.PrometheanWorld.com/Warranty
Support	Online Support for all Promethean Products available from: www.PrometheanKB.com

ActiView 324 SS 02/14 V1.2

©2014 Promethean Limited. All rights reserved. Promethean Ltd. is owner of a number of trademarks in several jurisdictions across the world. Any third-party product and company names are mentioned for identification purposes only and may be trademarks of their respective owners. [†]Applicable Terms and Conditions for warranty and support available at www.PrometheanWorld.com/ActivCare. All dimensions +/- 5mm (0.2in). All weights +/- 0.9kg (2lb). Product Specifications are subject to change without notice. www.PrometheanWorld.com